

UNIVERSAL INDUSTRIAL PRODUCTS, INC.

ONE COREWAY DRIVE, PIONEER, OH 43554-0628 USA * (419) 737-2324 * (800) 922-6957

Care and Maintenance of SOSS® Invisible Hinges

SOSS[®] Invisible Hinges are shipped already lubricated and under normal conditions, require no additional care.

If needed, we recommend a spray lubricant, such as WD-40, which serves both as a lubricant and cleaner. Apply gently, taking care not to overspray on the door or frame. Once applied, wipe with a soft cloth.

Do not use cleaning agents, solvents, or products like Brasso, because they can damage the finish and /or gum up the hinge links.

The following chemicals are not to be used on any SOSS hinge models with nylon links including, but not limited to the model #204, #208, #212, #216, #216FR, #218, #218FR, #220, #220FR:

Acetic Acid Conc.	Phenol, Aqueous
Acetic Acid 10%	Phosphoric Acid 10%
Boric Acid 10%	Potassium Permanganate 1%
Calcium Chloride 10%	Sodium Hydroxide Solution 50%
Chloroform	Sodium Hydroxide Solution 5%
Formic Acid 10%	Sulphuric Acid 98%
Hydrochloric Acid 36%	Tincture of Iodine (alc.)
Hydrochloric Acid 2%	Ozone
Hydrofluoric Acid	Nitric Acid 2%
Hydrogen Peroxide 30%	Lactic Acid 2%
Hydrogen Peroxide 0.5%	Hydrogen Sulphide